

# PCB Fuse Clips for ATC/ATM Blade, 5mm, 1/4" & 13/32" Diameter Fuses


## 1AXXXX Series

### For 1/4" Diameter Fuses

#### 1A1119 Series\*\*\*

With End Stops and Angled In leads

#### Dimensional Data




| Catalog Number | Clip Mat.*            | Finish     |
|----------------|-----------------------|------------|
| 1A1119-04      | High Performance Cu** | Bright Tin |
| 1A1119-05      | High Performance Cu** | Silver     |
| 1A1119-10      | Cart. Brass           | Bright Tin |

RoHS

#### 1A1120 Series\*\*\*

Without End Stops and Angled In Leads

#### Dimensional Data




| Catalog Number | Clip Mat.*            | Finish     |
|----------------|-----------------------|------------|
| 1A1120-02      | Cart. Brass           | Bright Dip |
| 1A1120-05      | High Performance Cu** | Silver     |
| 1A1120-06      | High Performance Cu** | Bright Tin |
| 1A1120-09      | Cart. Brass           | Bright Tin |

RoHS

#### 1A1907 Series\*\*\*

With End Stops & Straight Leads

#### Dimensional Data




| Catalog Number | Clip Mat.*            | Finish             |
|----------------|-----------------------|--------------------|
| 1A1907-02      | Cart. Brass           | None Bright Dipped |
| 1A1907-03      | High Performance Cu** | Bright Tin         |
| 1A1907-05      | High Performance Cu** | Silver             |
| 1A1907-06      | Cart. Brass           | Bright Tin         |

RoHS

#### 1A3398 Series\*\*\*

Without End Stops & Straight Leads

#### Dimensional Data




| Catalog Number | Clip Mat.*  | Finish     |
|----------------|-------------|------------|
| 1A3398-07      | Cart. Brass | Bright Tin |

RoHS

#### 1A4534 Series\*\*\*

With End Stops & Angled Out Leads

#### Dimensional Data




| Catalog Number | Clip Mat.*            | Finish     |
|----------------|-----------------------|------------|
| 1A4534-01      | High Performance Cu** | Bright Tin |
| 1A4534-06      | Cart. Brass           | Bright Tin |

RoHS

#### 1A4533 Series\*\*\*

Without End Stops & Angled Out Leads

#### Dimensional Data



| Catalog Number | Clip Mat.*            | Finish     |
|----------------|-----------------------|------------|
| 1A4533-01      | High Performance Cu** | Bright Tin |
| 1A4533-06      | Cart. Brass           | Bright Tin |

RoHS

\*Spg. Br. - Spring Bronze; BeCu - Beryllium Copper; Cart. Brass - Cartridge Brass

\*\*BeCu or High Performance Cu recommended for currents higher than 15 amps.

\*\*\*For RoHS compliant version add "-R" option code suffix to part number.


# PCB Fuse Clips for ATC/ATM Blade, 5mm, 1/4" & 13/32" Diameter Fuses

## 1AXXXX Series

### For 5mm Diameter Fuses

#### 1A5601 Series (0 to 7 amps)

##### Dimensional Data




| Catalog Number | Clip Mat.*  | Finish     |
|----------------|-------------|------------|
| 1A5601         | Cart. Brass | Bright Tin |

RoHS

#### 1A3399 and 1A5018 Series\*\*\*

##### With Straight Leads

##### Dimensional Data




| Catalog Number | Clip Mat.* | Finish     |
|----------------|------------|------------|
| 1A3399-10      | Spg. Br.   | Bright Tin |
| 1A3399-01      | BeCu**     | Silver     |
| 1A3399-04      | BeCu**     | Bright Tin |

RoHS


#### 1A5602 Series (0 to 7 Amps)

##### Dimensional Data



| Catalog Number | Clip Mat.   | Finish     |
|----------------|-------------|------------|
| 1A5602         | Cart. Brass | Bright Tin |

RoHS



##### High Profile

| Catalog Number | Clip Mat.* | Finish     |
|----------------|------------|------------|
| 1A5018-10      | Spg. Br.   | Bright Tin |
| 1A5018-7       | Spg. Br.   | Silver     |

##### Specifications

5mm PCB Mount Fuseclips  
 Current Rating: 15A  
 Voltage Rating: 500Vac  
 PCB Terminals: Solder Lug

\*Spg. Br. - Spring Bronze; BeCu - Beryllium Copper; Cart. Brass - Cartridge Brass.


\*\*BeCu recommended for currents higher than 15 amps.

### For 13/32" Diameter Fuses


#### 1A3400 Series\*\*\*

##### With End Stops & Straight Leads

##### Dimensional Data



1A3400-09 & 1A3400-10



1A3400-12

##### Specifications:


| Catalog Number | Clip Material    | Finish     | Amp Rating |
|----------------|------------------|------------|------------|
| 1A3400-09      | Spring Bronze    | Bright Tin | 20A Max.   |
| 1A3400-10      | Beryllium Copper | Silver     | 30A Max.   |
| 1A3400-12      | Spring Brass     | Bright Tin | 15A Max.   |

\*\*\*For RoHS compliant version add "-R" option code suffix to part number.

# PCB Fuse Clips for ATC/ATM Blade, 5mm, 1/4" & 13/32" Diameter Fuses


## 1AXXXX Series

ATM Fuses  
1A5778 Series  
Dimensional Data



MATERIAL: BRASS, NICKEL PLATED, .30 THICK  
.012


## 1A5779 Series



### SPECIFICATIONS


|                    |                                    |
|--------------------|------------------------------------|
| FUSECLIPS          | BRASS, NICKEL PLATED               |
| BASE MATERIAL      | GLASS FILLED NYLON, UL RATED 94V-0 |
| CURRENT RATING     | 15 AMPS                            |
| VOLTAGE RATING     | 500V AC                            |
| TEMPERATURE RATING | -50°C TO 145°C<br>-58°F TO 292°F   |

ATC Fuses (0 to 20 Amps)  
1A5600 Series  
Dimensional Data



| Catalog Number | Clip Mat.*  | Finish           |
|----------------|-------------|------------------|
| 1A5600         | Cart. Brass | Satin Finish Tin |

1A5780 Series  
Dimensional Data



### SPECIFICATIONS

|                    |                                    |
|--------------------|------------------------------------|
| FUSECLIPS          | BRASS, NICKEL PLATED               |
| BASE MATERIAL      | GLASS FILLED NYLON, UL RATED 94V-0 |
| CURRENT RATING     | 15 AMPS                            |
| VOLTAGE RATING     | 500V AC                            |
| TEMPERATURE RATING | -50°C TO 145°C<br>-58°F TO 292°F   |

\*Spg. Br. - Spring Bronze; BeCu - Beryllium Copper; Cart. Brass - Cartridge Brass

\*\*\*For RoHS compliant version add "-R" option code suffix to part number.


## PCB Fuse Clips for ATC/ATM Blade, 5mm, 1/4" &amp; 13/32" Diameter Fuses

## 1AXXXX Series

## Fuse Clip Catalog Numbers

## Footprint

## Dimensional Data



## Dimensions

| Catalog Number | A                |                   |                    |                     |                     |                               | ATC              | ATM               | B<br>Tabs                    | C<br>(4 holes)                | Board Thickness                   |
|----------------|------------------|-------------------|--------------------|---------------------|---------------------|-------------------------------|------------------|-------------------|------------------------------|-------------------------------|-----------------------------------|
|                | 7/8"<br>(22.2mm) | 1"<br>(25.4mm)    | 1 1/4"<br>(31.8mm) | 1 5/8"<br>(34.93mm) | 1 1/2"<br>(38.10mm) | 20mm                          |                  |                   |                              |                               |                                   |
| 1A5778-        | —                | —                 | —                  | —                   | —                   | —                             | —                | 0.464"<br>(11.79) | 0.144"<br>(3.66)             | 0.065"±0.002"<br>(1.65±0.05)  | 0.062"<br>(1.57)                  |
| 1A5779-        | —                | —                 | —                  | —                   | —                   | —                             | —                | 0.464"<br>(11.79) | 0.144"<br>(3.66)             | 0.065"±0.002"<br>(1.65±.05)   | 0.062"<br>(1.57)                  |
| 1A5780-        | —                | —                 | —                  | —                   | —                   | —                             | 0.560<br>(14.22) | —                 | 0.200"<br>(5.08)             | 0.100"±0.002"<br>(2.54±0.05)  | 0.062"<br>(1.57)                  |
| 1A3398-        | 1.00"<br>(25.40) | 1.125"<br>(28.58) | 1.375"<br>(34.920) | —                   | —                   | —                             | —                | —                 | 0.295"-0.305"<br>(7.49-7.75) | 0.067"-0.070"<br>(1.70-1.78)  | 0.093"<br>(2.36)                  |
| 1A1907-        | —                | —                 | —                  | —                   | —                   | —                             | —                | —                 | 0.295"-0.305"<br>(7.49-7.75) | 0.093"±0.002"<br>(2.36±0.05)  | 0.062"to 0.125"<br>(1.57to3.18)   |
| 1A1119-        | 1.00"<br>(25.40) | 1.125"<br>(28.58) | 1.375"<br>(34.92)  | —                   | —                   | —                             | —                | —                 | 0.295"-0.305"<br>(7.49-7.75) | 0.093"±0.002"<br>(2.36±0.05)  | 0.062"to 0.125"<br>(1.57 to 3.18) |
| 1A1120-        | 1.00"<br>(25.40) | 1.125"<br>(28.58) | 1.375"<br>(34.920) | —                   | —                   | —                             | —                | —                 | 0.295"-0.305"<br>(7.49-7.75) | 0.093"±0.002"<br>(2.36±0.05)  | 0.062"to 0.125"<br>(1.57 to 3.18) |
| 1A3399-        | —                | —                 | —                  | —                   | —                   | 0.875"<br>(22.23)             | —                | —                 | 0.200"<br>(5.08)             | 0.067"-0.070"<br>(1.70-1.78)  | 0.093"<br>(2.36)                  |
| 1A3400-        | —                | —                 | —                  | 1.50"<br>(38.10)    | 1.625"—<br>(41.28)  | —                             | —                | —                 | 0.405"<br>(10.29)            | 0.091"-0.095"<br>(2.31-2.41)  | 0.125"<br>(3.18)                  |
| 1A4533-        | 1.00"<br>(25.40) | 1.125"<br>(28.58) | 1.375"<br>(34.920) | —                   | —                   | —                             | —                | —                 | 0.300"<br>(7.62)             | 0.067"-0.070"<br>(1.70-1.78)  | 0.062"<br>(1.57)                  |
| 1A4534-        | 1.00"<br>(25.40) | 1.125"<br>(28.58) | 1.375"<br>(34.920) | —                   | —                   | —                             | —                | —                 | 0.300"<br>(7.62)             | 0.067"-0.070"<br>(1.70-1.78)  | 0.062"<br>(1.57)                  |
| 1A5018-        | —                | —                 | —                  | —                   | —                   | 0.820"±0.015"<br>(20.80±0.38) | —                | —                 | 0.180"<br>(4.6)              | 0.053"-0.002"<br>(1.35-0.05)  | 0.093"<br>(2.36)                  |
| 1A5600-        | —                | —                 | —                  | —                   | —                   | —                             | —                | —                 | 0.200"<br>(5.08)             | 0.052"±0.003"<br>(1.32±0.077) | 0.125"max.<br>(3.18)              |
| 1A5601-        | —                | —                 | —                  | —                   | —                   | 0.820"±0.015"<br>(20.80±0.38) | —                | —                 | 0.266"<br>(6.76)             | 0.067"±0.003"<br>(1.70±0.074) | 0.062"<br>(1.57)                  |
| 1A5602-        | —                | —                 | —                  | —                   | —                   | —                             | —                | —                 | 0.220"<br>(5.588)            | —                             | 0.125"max.<br>(3.175)             |

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.